



# 24/7 Plus

## STONE & CONCRETE SEALER WATER-BASED



**Sure Seal® 24/7 Plus Stone & Concrete Sealer** is a water-based penetrating sealer which provides unparalleled protection against water and oil-based stains, efflorescence and alkalis to maintain the natural look and beauty of stone surfaces.

**Sure Seal® 24/7 Plus Stone & Concrete Sealer** allows the treated surface to breathe and will not pool, discolour, etch or yellow the treated surface.

Excellent for use on all types of stone and masonry surfaces, including bluestone, slate, sandstone, limestone, travertine, terracotta, concrete, brick, stucco, pavers, exposed aggregate, terrazzo, etc. Formulated with exclusive resins this sealer penetrates even dense substrates such as marble, granite and porcelain and protects from moisture intrusion on both interior and exterior surfaces.

### KEY FEATURES

**Sure Seal® 24/7 Plus Stone & Concrete Sealer** was developed as an environmentally friendly, water based, silicone free product providing U.V. protection. It is invisible upon application and will preserve and not alter the natural look or finish of the surface being protected. The superior sealing properties promote easier clean-up since the foreign matter cannot penetrate and bond with the masonry surface.

### BENEFITS & CHARACTERISTICS:

- Water based, and V.O.C. compliant
- Non-toxic, Non-flammable
- Environmentally friendly
- Invisible impregnator with low odour
- Protects against oil and water-based stains
- Promotes easier cleanup
- Contains no silicones & non-yellowing
- Inhibits efflorescence and freeze thaw
- Preserves natural look
- Deep penetrating protection
- Interior and exterior use
- Cures fully in 24 hours

### Pack Size:

Available in 1, 4 & 20 Litre containers



**Sure Seal® Sealants  
Australia Pty Ltd.**

ABN 37 609 038 575





# Sure Seal® Sealants

## TECHNICAL INFORMATION:

**Description:** **Sure Seal® 24/7 Plus Stone & Concrete Sealer** is a superior water-based penetrating sealer that protects all porous stone surfaces against oil and water-based staining.

### Application:

**USE AS IS. DO NOT DILUTE.** Always ensure that the surface is clean and free from debris and previous sealants and waxes. Any existing stains must be removed prior to sealant application. Apply by brush, lambs-wool applicator or garden-type sprayer. One good coat is usually sufficient. However, on very porous surfaces or heavy walkway areas, two coats are recommended. Allow 1-2 hours between applications of each coat.

### Maintenance:

To clean exterior treated areas, use a garden hose with a pressure nozzle or pressure washer with a maximum pressure of 1000 PSI depending upon the surface. For interior applications simply mop or wipe with a soft cloth or sponge and a mild liquid cleaner or water. Do not use harsh cleaning agents such as abrasive powders, ammonia, acids, bleach, solvents or abrasive scrubbing pads.

### Cleaning Up of Equipment:

Rinse equipment with warm or cold water.

### Coverage:

One litre will cover approximately 8-40 sq. metres, depending upon the porosity of the substrate and method of application.

#### Disclaimer:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge. As the storage, handling and application of this material is beyond our control, we can only be responsible for the quality of our product at the time of dispatch. We reserve the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. It is the responsibility of the end user to determine the suitability of this material for any particular application

### Expected Wear:

**Sure Seal®** will last for many years with proper maintenance on all treated surfaces: however, heavy walkway areas should be tested yearly and product reapplied if necessary.

### Technical Data:

Physical Description & Colour: Amber coloured liquid

Odour: Mild odour

Volatility: No data

### Storage/Shelf Life:

Keep sealed in original containers and store in a cool dry place. When properly stored, shelf life is a minimum of six months from date of opening the container. Do not allow to freeze. Do not apply to surfaces below 8 deg. °C.

### ADG Code:

This product is not classified as a Dangerous Good. No special transport conditions are necessary unless required by other regulations.

### Note:

Consult the Safety Data Sheet for full technical and safety details. It is recommended to test the product first on a small inconspicuous area to determine its efficacy or unexpected results.



**Sure Seal® Sealants  
Australia Pty Ltd.**

ABN 37 609 038 575